16871 Chagrin Blvd. Suite 434 Shaker Heights, OH 44120

Section 1 – Identification

Product Name: Dream 5% Sodium Fluoride 3D Dental Design & Development LLC Manufacturer:

Varnish/

Toll Free: (877) 605-8061 **Active Ingredient:** Sodium Fluoride Emergency Phone Numbers: US & Canada: (800)424-9300

Family: Fluoride Treatment

Product Use: Professional Dental Preventive Care

Product #: Various

Section 2 – Hazards Identification

Health:

Acute Toxicity - Category 4 - H302 - Harmful if swallowed Skin Irritant – Category 2 – H315 – Causes skin irritation Eye Irritant – Category 2B – H320 – Causes eye irritation

Exposure - Category 3 - H335-336 - May cause respiratory irritation, May cause drowsiness or dizziness

Environmental:

Non-Hazardous

Physical:

Flammable Liquid - Category 3 - H225 - Highly flammable liquid and vapor

Label Elements:

GHS Label Elements:

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard Pictograms:







Section 3 – Composition/Information on Ingredients

Chemical Identity	CAS Numbers	EINECS#	Substance Classification 67/548/EEC (EC) No. 1272/2008	%
Sodium Fluoride	7681-49-4	231-667-8	Acute Toxicity – Category 4 – H302 Skin Irritant – Category 2 – H315 Eye Irritant – Category 2B – H320 Exposure – Category 3 – H335-336	5%
Ethanol	64-17-5	200-578-6	Flammable Liquid – Category 3 – H225	25% - 35%
Synthetic Resin	Proprietary	Proprietary	Skin Irritant – Category 2 – H315	<60%

See Section 16 for Hazard and Precautionary Statement Key.

Section 4 – First Aid Measures

Routes of Exposure	First Aid Instructions
--------------------	------------------------

]	Page	e 2	of	(

Eye	Immediately flush with water for 15 minutes, holding the eyelids apart. Get medical help if discomfort persists.
Skin	Wash thoroughly with soap and water. Remove contaminated clothing. Get medical help if discomfort persists.
Ingestion	If greater than normal dose is swallowed, do not induce vomiting. Drink large quantity of water, milk or milk of magnesia. Contact Poison Control.
Inhalation	None needed under normal use conditions. If irritation develops, move to fresh air. Get medical attention if symptoms persist.

Section 5 – Fire Fighting Measures

Extinguishing Media:	Carbon dioxide, dry chemical foam, alcohol-resistant foam. Do not use water.
Fire Fighting Instructions:	During a fire, irritating or highly toxic gases may be generated by thermal decomposition. If potential for exposure, wear complete personal protective equipment including self contained breathing apparatus, with full face operated in pressure demand.
Unusual Hazards:	Evacuate all personnel.

Section 6 – Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures:	Remove people from danger area. Keep away from ignition sources. Wear protective clothing, eye protection, gloves and respiratory protective device. Avoid contact with eyes and skin.				
Environmental Precautions:	Do not allow product to reach sewage system or any water course. Do not allow to penetrate the ground. Report releases as required by local and national authorities.				
Methods and Materials for Containment and Clean-up:	Ensure adequate ventilation. Collect using an inert non-combustible absorbent material and place in appropriate containers for disposal.				

Section 7 – Handling and Storage

Precautions for Safe Handling:	Ensure good ventilation/exhaustion at the workplace. Avoid contact with the eyes and skin. Avoid breathing vapors. Keep product away from hear, sparks, flames and other sources of ignition. Use in accordance with package instructions.
I Conditions for Nate Morage.	Store in a cool, well ventilated area away from oxidizing agents and direct sunlight. Avoid excessive heat and ignition sources. Do not store together with acids.

Section 8 – Exposure Controls / Personal Protection

Occupational Exposure Limits:

o comparisonar Empostar o Em	1	
Sodium Fluoride	France Spain Italy	 0.5mg/m3 ACGIH TLV TWA, 2.5mg/m3 US OSHA PEL TWA 2.5mg/m3 TWA EU IOEL 2.5mg/m3 TWA UK OEL 2mg/m3 INRS VME 2.5mg/m3 VLA-ED 2.5mg/m3 8 hr. Value Limit 2.5mg/m3 TWA EU IOEL
Ethanol	United States Germany United Kingdom France Spain Italy European Union	 1000 ppm TWA INRS VME, 5000 ppm VLCT 1000 ppm TWA VLA-ED None Established

Page 3 of 6	Page	3	of	(
-------------	------	---	----	---

Synthetic Resin	United States Germany United Kingdom France Spain Italy European Union	 None Established
Engineering Controls	Use with adequate	general and local ventilation to minimize exposure levels.

Personal Protective Equipment:

General Measures:	To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product.
Eye/ Face Protection:	Safety glasses / goggles or splash shields are required when handling. Ensure eye bath is on hand.
Skin Protection:	Use impermeable clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit.
Respiratory Protection:	In case of insufficient ventilation, wear suitable respiratory equipment.
Thermal Hazards:	Not Applicable

Section 9 – Physical and Chemical Properties

Appearance Odor & Odor Threshold			PH Relative Density		Viscosity	% Volatile				
Off-White Visco	ous Liquid		Product Specific		6.6	j	1.1 g/ml	<6000cps	s N/A	
Boiling Point/ Freezing Point (°F/°C)	Freezing Point Decomposition		Octanol/Water Partitioning Coefficient Log Po/w Vapo Pressur			Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)	
170/79	N/DA		Log Po/w		N/D	PΑ	N/DA	N/DA	N/A	N/A

Flash Point (°F/°C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)	Explosion Limits
56/14	N/A	N/A	LEL: 3.5 UEL: 15.0

Section 10 – Stability and Reactivity

Chemical Stability: Stable at ambient temperature	Incompatible Materials: Avoid oxidizing agents	
Possibility of Hazardous Reactions: None known	Hazardous Decomposition Products: None Known	
Conditions to Avoid: Keep away from heat, sparks and all ignition sources.		

Section 11 – Toxicological Information

Acute Toxicity:

LD/LC50 values that are relevant for classification: No further relevant information available.

Primary irritant effect:

on the skin: Irritant to skin and mucous membranes.

on the eye: Irritating effect.

Sensitization: No sensitizing effects known.

Page 4 of 6

Experience with humans:

May cause damage to central nervous system.

May cause damage to liver.

May cause damage to lungs.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

Carcinogenic categories:

IARC (International Agency for Research on Cancer)		
Ethanol	1	
Sodium Fluoride	3	
Synthetic Resin	3	

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Carcinogenic categories' legend:

IARC Group 1: The agent is carcinogenic to humans.

IARC Group 2A: The agent is probably carcinogenic to humans.

IARC Group 2B: The agent is possibly carcinogenic to humans.

IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.

IARC Group 4: The agent is probably not carcinogenic to humans.

NTP K: Known to be human carcinogen.

NTP R: Reasonably anticipated to be human carcinogen.

Additional carcinogenic information:

The substance ethanol is listed by IARC as a Group 1 carcinogen but in alcoholic beverage consumption. IARC Volume 100E (2012) "Personal Habits and Indoor Combustions" stated in its monograph "Consumption of Alcoholic Beverages" the following evaluation: "Ethanol in alcoholic beverages is carcinogenic to humans (Group 1).

Section 12 – Ecological Information

Toxicity:	Sodium Fluoride: 96hr LC50 Oncorhynchus mykiss (Rainbow trout) 83.7 mg/L, 48hr EC50 daphnia magna 98 mg/L. Ethanol: 96hr LC50 fathead minnow 4,200 mg/L, 48hr EC50 daphnia magna Synthetic Resin: 48hr EC50 daphnia magna > 1.5mg/L	
Persistence and Degradability:	Biodegradation is not applicable to inorganic substances such as sodium fluoride. Ethanol: Readily biodegradable (84% after 20 days). Synthetic Resin: has been shown to degrade > 25% in 28 days.	
Bio-accumulative Potential:	No data is available.	
Mobility in Soil:	Ethanol has a high mobility in soil.	
Other Adverse Effects:	No data available.	
Results of PBT/vPvB Assessment:	No data available.	

Section 13 – Disposal Considerations

Regulations:	Dispose in accordance with local and national environmental regulations.	
Properties (Physical/Chemical) Affecting Disposal:	None known.	
Waste Treatment Recommendations:	None needed for normal anticipated use.	

Page 5 of 6

Section 14 – Transport Information

UN Number: UN1170				
UN proper shipping name: AD	R/RID: Ethanol			
IMI	OG: Ethanol			
IAT	A: Ethanol			
DOT: Ethanol				
UN Number:	ADR/RID:	IMDG:	IATA:	DOT:
Transport hazard class(es):	3	3	3	3
Packaging group:	II	II	II	II
Environmental hazards:	No	Marine Pollutant: No	No	No
Special precautions for user:	Not Applicable			

Section 15 – Regulatory Information

US Federal Regulations

Clean Air Act: HAP/ODS	This product contains the following HAP's or ODS: None
Clean Water Act: Priority Pollutant	This product contains the following chemicals listed under the U. S. Clean Water Act Priority Pollutant and Hazardous Substance List: None
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and /or other applications as an indirect food-packaging additive.
Occupational Safety and Health Act	This product is not considered to be hazardous under the OSHA Hazard Communication Standard.
RCRA This product contains the following chemicals considered to be hazardous was under RCRA (40 CFR 261). None	
SARA Title III: Section 302 (RQ)	This product contains no chemicals regulated under Section 302 as extremely hazardous substances.
SARA Title III: Section 302 (TPQ)	This product contains chemicals regulated under Section 304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List): • Sodium Fluoride – CAS #7681-49-4 1000 # RQ
SARA Title III: Section 311-312:	This product is considered to be hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). It's hazards are: • Sodium Fluoride – CAS# 7681-49-4 (Corrosive)
SARA Title III: Section 313:	This product contains the following chemicals which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: None
TSCA Section 8(b): Inventory:	This product does contain chemicals listed on the TSCA inventory or otherwise complies with TSCA pre-manufacture notification requirements.
TSCA Significant New Use Rule:	Sodium Fluoride – CAS# 7681-49-4 None of the chemicals in this material have a SNUR under TSCA.

State Regulations:

California: This product does not contain chemicals known to the State of California to cause cancer, birth defects or reproductive harm.

International Regulations

CDSL: Canadian Inventory (on Canadian Transitional List)	Sodium Fluoride – CAS# 7681-49-4
EU REACH: This product is a medicinal product and not subject to registration requirements.	

Section 16 – Other Information

Abbreviations and acronyms:		
GHS:	GHS: Globally Harmonized System of Classification and Labeling of Chemicals	
HCS:	Hazard Communication Standard (USA)	
SDS:	Safety Data Sheet	
ECHA:	European Chemicals Agency	
OSHA:	Occupational Safety and Health Administration	
ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road	
IMDG:	International Maritime Code for Dangerous Goods	
DOT:	US Department of Transportation	
IATA:	International Air Transport Association	
ACGIH:	American Conference of Governmental Industrial Hygienists	
CAS:	Chemical Abstracts Service (division of the American Chemical Society)	
NFPA:	National Fire Protection Association	
HMIS:	Hazardous Materials Identification System	
VOC:	Volatile Organic Compounds	
LC50:	Lethal Concentration, 50%	
LD50:	Lethal Dose, 50%	
PBT:	Persistent, Bioaccumulative and Toxic	
vPvB:	very Persistent and very Bioaccumulative	
Xi:	Irritant	
T:	Toxic	
F:	Highly Flammable	

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This SDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the SDS may not be applicable.

3D Dental components are provided on an as is basis without warranties of any kind either expressed or implied. 3D Dental does not warrant the use or the results of use of the materials sold on an as is basis since they are intended for remanufacturing or repackaging. It is the sole responsibility of the user to examine and determine appropriate application and regulatory requirements associated with said 3D Dental components.